

TAILORMADE LOFT LADDERS

SOGEM

FIRE PRO REI 45

fire resistant 45 min (standard incl. plastic feet and frame)

- Stair cavity (length) :

min. 112cm / max. 160cm

- Stair cavity (width) :

min. 50cm / max. 80cm

• Length x width of stair cavity must be max. 1,12m² (example : stair cavity of 140x80cm – 1,40m x 0,80m = 1,12m²)

- Floor to ceiling height:

min. 218cm / max. 336cm

• If floor to ceiling height > 264cm, length of stair cavity must be minimum 115,5cm
• If floor to ceiling height > 288,5cm, length of stair cavity must be minimum 140cm

- Casing height :

min. 19cm / max 80cm

• Provide 1 extra step in casing from 36cm
• Provide 2 extra steps in casing from 65cm

- 3 sections folding loft ladder

OPTION :

- Red handrail

(width of stair cavity must be \geq à 60cm)



▲ FIRE PRO REI 45

ISOCLIC PRO 76

(standard incl. plastic feet and frame)

- Stair cavity (length) :

min. 101,5cm / max. 160cm

- Stair cavity (width):

min. 50cm / max. 100cm

• If width of stair cavity \leq 56,3cm, length of stair cavity must be \geq 120cm

- Floor to ceiling height :

min. 204cm / max. 322cm

• If floor to ceiling height > 274cm, length of stair cavity must be \geq 140cm
• If length + width of stair cavity = 244,9cm, floor to ceiling height must be max. 274cm (12 steps)

- Casing height :

min. 24cm / max 80cm

• Provide 1 extra step in casing from 36cm
• Provide 2 extra steps in casing from 65cm

- 3 sections folding loft ladder

if length of stair cavity \geq 120cm

- 4 sections folding loft ladder

if length of stair cavity \geq 119,9cm

OPTION :

- Red handrail

(width of stair cavity must be \geq à 60cm)



▲ ISOCLIC PRO 76

ISOCLIC PRO CONFORT

(standard incl. adjustable feet, frame and telescopic handrail)

- Stair cavity (length) :

min. 120cm / max. 160cm

- Stair cavity (width) :

min. 60cm / max. 100cm

• Length + width of stair cavity must not exceed 244,9cm

- Floor to ceiling height :

min. 222,4cm / max. 284,6cm

• If floor to ceiling height > 264,4cm, length of stair cavity must be \geq 130cm
• If floor to ceiling height > 278cm, length of stair cavity must be \geq 140cm

- Casing height :

min. 24cm / max 80cm

• Provide 1 extra step in casing from 36cm
• Provide 2 extra steps in casing from 65cm

- 3 sections folding loft ladder

OPTION :

- Additional telescopic handrail



▲ ISOCLIC PRO CONFORT

TAILORMADE LOFT LADDERS

SOGEM

1. Stair cavity (length) :
2. Stair cavity (width) :
3. Floor to ceiling height :
4. Ceiling height (or casing height) :

CHOICE OF LOFT LADDER



Fire Pro REI 45



Isoclic Pro 76



Isoclic Pro Confort

